

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Claims 1-52 (Canceled).

53. (New) A mask assembly for delivering breathable gas to a patient, comprising:
a frame including a central portion, a first side portion provided to a first lateral side of the central portion, and a second side portion provided to a second lateral side of the central portion;
a sealing member provided to the central portion of the frame and adapted to form a seal with the patient's nose in use;
first and second inlet conduits, each inlet conduit having a first end and a second end;
first and second angled connectors, the first angled connector provided between the first end of the first inlet conduit and the first side portion of the frame, and the second angled connector provided between the first end of the second inlet conduit and the second side portion of the frame;
a generally Y-shaped connector that interconnects the inlet conduits with a supply of breathable gas, the Y-shaped connector including a first connector portion to engage the second end of the first inlet conduit and a second connector portion to engage the second end of the second inlet conduit, the first connector portion being angled with respect to the second connector portion; and
a headgear assembly to support the frame and the sealing member in a desired position on the patient's face, the headgear assembly including a pair of straps and a rear portion.

54. (New) The mask assembly according to claim 53, wherein the sealing member is removably coupled to the central portion of the frame.

55. (New) The mask assembly according to claim 54, wherein the frame and the sealing member form at least a portion of a sub-assembly that is angularly adjustable relative to the headgear assembly.

56. (New) The mask assembly according to claim 55, further comprising a plurality of visual indicators which can be selectively matched with a reference indicator provided adjacent the visual indicators to indicate a degree of angular adjustment.

57. (New) The mask assembly according to claim 56, wherein the plurality of visual indicators includes a plurality of spaced apart arrows and the reference indicator includes an arrow.

58. (New) The mask assembly according to claim 57, wherein the rear portion includes an upper strap portion and a lower strap portion that cooperate to define an opening through which an occiput region of the patient's head at least partially protrudes in use.

59. (New) The mask assembly according to claim 58, wherein the straps extend superior to the patient's ears in use.

60. (New) The mask assembly according to claim 59, wherein the central portion of the frame includes a central opening that accommodates the sealing member.

61. (New) The mask assembly according to claim 60, wherein the frame includes openings for CO₂ washout.

62. (New) The mask assembly according to claim 61, wherein the sealing member includes a nasal cushion.

63. (New) The mask assembly according to claim 62, further comprising a headgear connector to interconnect the frame with the headgear assembly.

64. (New) The mask assembly according to claim 63, wherein the frame and the sealing member are angularly adjustable relative to the headgear connector.

65. (New) The mask assembly according to claim 64, further comprising an indexing section structured to allow selective ratcheting adjustment of the frame and the sealing member relative to the headgear assembly while remaining locked in an adjusted position during use.

66. (New) The mask assembly according to claim 53, further comprising slotted connectors provided to the frame, wherein each of the straps includes an end that is structured to be threaded through a respective slotted connector.

67. (New) A mask assembly for delivering breathable gas to a patient, comprising:
a main conduit portion including a central portion, a first side portion provided to a first lateral side of the central portion, and a second side portion provided to a second lateral side of the central portion, the first side portion defining a first inlet opening and the second side portion defining a second inlet opening;

a sealing member provided to the central portion of the main conduit portion and adapted to form a seal with the patient's nose in use;

a gas washout vent provided to the central portion of the main conduit portion, opposite to the sealing member, the gas washout vent including a plurality of openings for gas washout;

first and second inlet conduits, each inlet conduit having a first end and a second end;

first and second connectors, the first connector provided between the first end of the first inlet conduit and the first inlet opening of the first side portion, and the second connector provided between the first end of the second inlet conduit and the second inlet opening of the second side portion;

a generally Y-shaped connector to interconnect the inlet conduits with a supply of breathable gas, the Y-shaped connector including a first connector portion to engage

the second end of the first inlet conduit and a second connector portion to engage the second end of the second inlet conduit, the first connector portion being angled with respect to the second connector portion;

an elongated member having a central portion that supports the main conduit portion and first and second side portions supporting slotted headgear connectors, the central portion including a pair of openings adapted to retain and locate the main conduit portion; and

a headgear assembly including headgear straps that are structured to be threaded through respective slotted headgear connectors.

68. (New) The mask assembly according to claim 67, wherein the first and second side portions of the elongated member are partially deformable so that the first and second side portions are flexible and bendable to conform with the patient's face.

69. (New) The mask assembly according to claim 68, wherein the elongated member is constructed of polymeric material.

70. (New) The mask assembly according to claim 69, wherein the elongated member is constructed of polypropylene.

71. (New) The mask assembly according to claim 70, wherein the sealing member includes a nasal cushion.

72. (New) The mask assembly according to claim 71, further comprising an indexing section structured to allow selective ratcheting adjustment of the main conduit portion relative to the headgear assembly while remaining locked in an adjusted position during use.

73. (New) A mask assembly for delivering breathable gas to a patient, comprising:
a frame including a central portion and first connector portions provided to lateral sides of the central portion;

a nasal cushion provided to the central portion of the frame and adapted to form a seal with the patient's nose in use;

second connector portions coupled to respective first connector portions;
and

a headgear assembly provided to the second connector portions and adapted to support the frame and the nasal cushion in a desired position on the patient's face, the headgear assembly including headgear straps each including an end that is structured to be threaded through a respective slotted connector supported by the second connector portions, wherein:

the frame and the nasal cushion form at least a portion of a sub-assembly that is angularly adjustable relative to the second connector portions and the headgear assembly,

a plurality of visual indicators are provided which can be selectively matched with a reference indicator provided adjacent the visual indicators to indicate a degree of angular adjustment, and

an indexing section structured to allow selective ratcheting adjustment of the first connector portions with respect to the second connector portions while remaining locked in an adjusted position during use.